

## Quotation of Amorphous solar module

Item No	Size(mm)	Voc(V)	Isc(mA)	Vop(V)	Iop(mA)
KS-A25W	1275*385*26mm	27	1660	18	1380
KS-A20W	1275*385*26mm	27	1330	18	1100
KS-A15W	850*385*26mm	27	990	18	830
KS-A10W	640*385*26mm	27	660	18	550
KS-A5W	322*385*18mm	27	330	18	270



Remark

Product Features

- Solar panel mounted with aluminum frame reinforce it's strength.
- Front glass encapsulate with polymer materials on solar panel back side, weather proof and water proof.
- Built-in blocking diode protects battery discharge at night
- Maintenance Free/Easy installation.
- Works in all weather condition.

Specification:

- Testing condition: Air Mass:AM1.5, illumination:1000W/m<sup>2</sup>, Temperature :25°C
- Dimension tolerance: ±5% ;
- Testing condition: AM1.5, 1000W/m<sup>2</sup>, 25°C.
- Operating temperature: -40 to +85°C;
- Relative Humidity: 0 to 100%
- Warranty: 90% output for 10 years, 80% output for 20 years
- SGS Certificate and CE Certificate

Office Address:

N0.601,ZhongKang Pioneer Park,ZhongKang Road,  
Futian District, ShenZhen City,Guangdong Province,China

Factory Address:

Longxi Hi-tech Industrial Park, Longcheng Road, Longgang  
Town, ShenZhen City,Guangdong Province,China



Tel: +86.755.8351 5659

Fax: +86.755.8271 6024

Website: <http://www.solars-china.com>

Email: [market@solars-china.com](mailto:market@solars-china.com)

MSN: [market@solars-china.com](mailto:market@solars-china.com)

Skype: KAXIDY